

Qualitatively superior dehumidifiers

AIR DRY

**STIELOW Dehumidifier
AIR DRY 2 D**



Standard equipment

- large water tank
- Water level indicator light
- automatic appliance switch-off when the water tank is full
- 1/2" threaded drain connection for permanent water drainage
- Transport bracket
- Industrial swivel castors
- Axial fan stepless
- alufume-tec-composite
- hot gas defrosting
- fully automatic operation
- operating hours counter

Extras

- electricity consumption meter
- V2A Housing
- Crane hook attached
- Air duct connections
- Wall bracket

- Sound-absorbing "Armstrong" version
- Aggregate sealing
- Power connection cable up to 30 m
- external humidity controller
- Dew point controller internal/external
- separate frost monitor
- Special paintwork according to RAL
- Special paintwork on request
- Tropical version (over 30°C)
- Condensate water pump 1.5 - 6.0 m delivery head
- Built-in fault indicator
- Data bus Remote monitoring
- Protection class IP 54

30% Energy saving!

DIGITAL CONTROL – illuminated display, 4 keys for easy programming, display correction individually selectable, hysteresis (humidity deviation) adjustable, response time of less than 1 second, self-diagnosis every second, visual error messages on the display, pre-programmed, self-calibrating, green dehumidification mode indicator light, orange defrosting indicator light, red warning light, water tank filled to maximum, illuminated main switch, operating hours counter, automatic hot gas defrosting, anodized transport handles, mobile on industrial swivel castors – highly stable, intake-side ventilation grille can be opened with VILEDON dust filter mat, reusable and washable.

65 litre class

800 cbm Volume

equipment make them superior. Special requests can be taken into account as extras.

Trust the original, don't make any compromises if your priority is to be able to dry reliably and permanently.

Low power consumption with maximum water extraction

STIELOW®

Advantage and Technology made in Germany

Trust the original

since 1952 by STIELOW

Dehumidifiers – in demand like never before !

Ideal for people and the environment




Technical Parameters:

AIRDRY 2 D

Max. Water removal	66,2
at +30°C / 70% r.H.	46,8
at +20°C / 70% r.H.	35,4
at + 8°C / 70% r.H.	13,8
Compressor PS / kW	0,5 / 0,37
Tension V/Hz	230/50
Power consumption /h	590 Watt
Cooling capacity kcal/h	2000
Air output cbm/h	840
Water tank	10 Liter
Work area °C	*-10 bis 40
Dimensions: Height/Depth/Width	870 / 630 / 440 mm
Net weight kg	57

*assuming that the bath and drain are heated separately



King Customer

Our service power – five strong advantages for you !

- Expert advice – everywhere on site.** Our specialist advisors are available nationwide to provide you with help and advice - it doesn't cost anything to ask!
- Service quickly on site throughout Europe.** Euro-Express service with pro rata travel allowance.
- Repair** – we will advise you on all questions relating to repairs and will repair your device in our master workshop with a cost estimate at fair prices, even if you did not buy it from us.
- Disposal** – if a repair is not required, we naturally guarantee the professional disposal of old appliances. A plus for the environment, a service for you.
- Guarantee** – 1 year for commercial use, 2 years for private use with price/performance guarantee - Made in Germany.



Hinged ventilation grille VILEDON dust filter mat



STIELOW GMBH

MASCHINEN- UND APPARATEBAU
Limburg Plant
Industriestrasse 2-4
65614 Beselich-Obertiefenbach
Fon 0049 64 84 / 91 21-0
Fax 0049 64 84 / 91 21-50
info@stielow.net · www.stielow.net

Germany's largest specialist company for air dehumidification and humidification
First German machine factory for transportable dehumidifiers