



STIELOW Dehumidifier AIRDRY T 50 D, aggregate



The STIELOW dehumidifier AIRDRY T 50 D, aggregate is designed as a console unit for ceiling mounting. A wall bracket is optionally available. Alternatively, the AIRDRY 2 D is available as a mobile stationary unit or the TG 50 P from the HANDYDRY series as a universally transportable unit with large castors.

No matter which design you choose: STIELOW dehumidifiers last longer than others and impress with their extreme value in daily operation, so that the appliances always remain operational even after long periods of use. Their robustness and favourable power consumption, combined with simple handling and complete equipment as standard, make them superior.

- ³/₄" threaded drain connection for permanent water drainage
- Industrial swivel castors
- Handle scales on both sides
- Axial fan stepless
- *aluframe-tec-composite*
- hot gas defrosting
- fully automatic operation
- operating hours counter

Options

- Electricity consumption meter
- V2A Housing
- Crane hook attached
- Wall bracket Sound-absorbing "Armstrong" version
- Aggregate sealing
- Power connection cable up to 30 m
- external humidity controller
- Dew point controller internal/external
- separate frost monitor Special paintwork
- according to RAL
- Special paintwork on request
- Tropical version (over 30°C)
- Condensate water pump 1.5 - 6.0 m delivery head
- Built-in fault indicator data bus remote monitoring
- Protection class IP 54



65 Liter-Klasse 800 cbm-Rauminhalt

Special requests can be considered as part of the extras.

Trust the original, don't make any compromises if your priority is to be able to dry reliably and permanently.

Low power consumption with maximum water extraction !





Germany's largest specialist company for air dehumidification and humidification First German machine factory for transportable dehumidifiers