STIELOW Dehumidifier AIRDRY T6D, T5D, T4D, T3D, T3-2D Aggregate for wall mounting

- the 4 swivel castors are removable -

Floor lineup is possible!

Standard equipment

- 1/2" threaded drain connection for permanent water drainage
- Removable industrial swivel castors
- Handle scales on both sides
- Axial fan stepless
- aluframe-tec-composite
- hot gas defrosting
- fully automatic operation
- operating hours counter

Extras

- Electricity consumption meter
- V2A Housing
- Crane hook attached
- Sound-absorbing "Armstrong" version
- Aggregate sealing
- Power connection cable up to 30 m
- external humidity controller
- Dew point controller internal/external
- separate frost monitor

16-55 litre class
150-700 cbm Volume

STIELOW AIRDRY dehumidifiers remain what they have always been - products of the highest quality.

Manufactured by hand since 1952 from hundreds of individual parts, the variety of models still requires manual production to this day.

Every single STIELOW dehumidifier is created with care and the highest standards of durability, with dedication and attention to detail - guaranteed!

That is why every STIELOW dehumidifier always remains something special.

Trust the original, don't make any compromises if your priority is to be able to dry reliably and permanently.

30% Energy Saving!

- Special paintwork according to RAL
- Special paintwork on request
- Tropical version (over 30°C)
- Condensate water pump 1.5 6.0 m delivery head
- Built-in fault indicator Data bus Remote monitoring
- Protection class IP 54

DIGITAL CONTROL – illuminated display, 4 buttons for easy programming, display correction individually selectable, hysteresis (humidity deviation) adjustable, response time of less than 1 second, self-diagnosis every second, visual error messages on the display, pre-programmed, self-calibrating, green dehumidification indicator light, orange defrost indicator light, illuminated main switch, automatic hot gas defrosting.

STIELOW®

Advantage and Technology made in Germany

Trust the original

since 1952 by STIELOW

Technical Parameters:					
AIRDRY	T6D	T5D	T4D	T3D	T3-2 D
Max. Water removal	16,1	27,4	33,1	47,5	55,1
at +30°C / 70% r.H.	10,0	17,7	24,5	30,1	39,0
at +20°C / 70% r.H.	7,8	10,0	12,2	18,7	29,5
at + 8°C / 70% r.H.	4,6	4,9	6,1	6,7	11,5
Compressor PS/kW	0,2/0,15	0,22/0,16	0,25/0,18	0,33/0,24	0,45/0,35
Tension V/Hz	230/50	230/50	230/50	230/50	230/50
Power consumption /h	200 Watt	290 Watt	330 Watt	420 Watt	550 Watt
Cooling capacity kcal/h	550	750	850	1100	1950
Air output cbm/h	450	480	500	650	750
Work area °C	*-10 to40	*-10 to40	*-10 to 40	*-10 to 40	*-10 to 40
Dimensions: Height/Depth/Width 415 / 455 / 605 mm					
Net weight kg	29,0	29,6	30,0	30,3	31,5
*assuming that the bath and drain are heated separately					



King Customer

Our service power – five strong advantages for you!

- 1. Expert advice everywhere on site. Our specialist advisors are available nationwide to provide you with help and advice - it doesn't cost anything to ask!
- 2. Service quickly on site throughout Europe. Euro-Express service with pro rata travel allowance.
- 3. Repair we will advise you on all questions relating to repairs and will repair your device in our master workshop with a cost estimate at fair prices, even if you did not buy it from us.
- 4. Disposal if a repair is not required, we naturally guarantee the professional disposal of old appliances. A plus for the environment, a service for you.
- 5. Guarantee 1 year for commercial use, 2 years for private use with price/ performance quarantee - Made in Germany.



Underside of appliance with hose connection, removable castors



Rear panel with wall mounting points



Device side view, air inlet side with handle scale









STIELOW GMBH MASCHINEN- UND APPARATEBAU

Limburg Plant Industriestrasse 2-4 65614 Beselich-Obertiefenbach Fon 0049 6484/9121-0 Fax 0049 6484/9121-50 info@stielow.net · www.stielow.net